Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

Specifications Bigsaver® Fire Compartments

Version 1.5 | June 1, 2025

HILTRA® BIGSAVER® MODEL BS, BS-L, BS-XL GENERAL

Design/Fire Resistance:

- The composite structure has been evaluated by the accredited testing institute Efectis®.
- Efectis fire resistance report: 94-CVB-R1178/2009-Efectis-R0834(Rev.1)/2010-Efectis-R1117-S.
- Designed as a self-contained fire compartment for the storage of packaged hazardous substances in accordance with the Building Decree and the PGS 15: 2025 guideline, version 1.0 (final/Jan. 2025).
- Fire resistance (WBDBO) of 60 minutes, determined in the event of a fire originating from the outside and a fire originating from the inside, based on all criteria of Measure M25 of PGS 15: 2025, version 1.0 (final/Jan. 2025)

Enclosure (walls, roof, and door):

- Enclosure constructed from galvanized sheet pile profiles.
- Interior lined with non-combustible and insulating material up to a height of 1100 mm, finished with galvanized sheet metal.
- The roof is equipped with an integrated rain gutter on both long sides.
- Equipped as standard with a lifting device suitable for transporting the unit when empty.
- Equipped as standard with a grounding connection.
- Single door compliant with EN 1634-1:2008 (EI160):
- The Bigsaver® model BS comes standard with a single-leaf door that is self-closing in the event of a fire.
- Door leaf equipped with a latch, panic bar, cylinder lock, and door closer, including an automatic Thermolock fire-sealing mechanism.
- Door jambs are fitted with fire-foaming strips, ensuring they are automatically sealed in the event of a fire.
- The door can be locked at an opening angle of approximately 90°; in the event of a fire, the Thermolock releases the lock and the door automatically closes into the door frame.
- Double door compliant with EN 1634-1:2008 (EI160):
- Bigsaver® models BS-L and BS-XL come standard with a double-leaf door that self-closes in the event of a fire.
- Right leaf with latch, panic bar, cylinder lock, and door closer including automatic Thermolock fire-closing mechanism.
- Left leaf on the inside with espagnolette lock and door closer including automatic Thermolock fire-closing mechanism.

- Door jambs are equipped with fire-sealing strips that expand in the event of a fire, ensuring the door is automatically sealed.
- The door can be locked at an opening angle of approximately 90°; in the event of a fire, the Thermolock disengages the lock and the door automatically closes into the door jamb.

Drip pan:

- Fully liquid-tight welded drip pan made of sheet steel, equipped with galvanized grating floor segments.
- Corrosion protection: SA2.5 blasting followed by a 100 µm Acraton zinc phosphate epoxy coating in RAL 7005/mouse gray.

Ventilation openings:

- Ventilation and exhaust through diametrically positioned ventilation openings, finished inside and out with galvanized louvered grilles.
- Equipped as standard with flame-retardant mesh and fire-resistant grilles, ensuring they close automatically in the event of a fire.

Hazard labeling:

- Hazard identification using pictograms in accordance with PGS 15, Ø and/or ? 200 mm, symbols: “flammable (liquid) substances” and “no fire, open flames, or smoking” (other pictograms available upon request).

Design options:

- Option A1: exterior, except for the top of the roof, finished with a 2K polyurethane coating in standard colors: RAL 3020/traffic red, RAL 5010/gentian blue, RAL 6002/leaf green, RAL 7035/light gray, or RAL 9001/cream white.
- Option A2: exterior, except for the top of the roof, finished with a 2K polyurethane coating in a non-standard RAL color (excluding traffic, luminescent, and metallic colors)
- Option C: Increase the capacity of the drip tray.
- Option D1A: Replace the single 1300 mm door with a double 1800 mm swing door.
- Option D2B: A 2700 mm double-leaf door instead of a single 1300 mm door.
- Option F: Flange ØxH=80x40 mm mounted in the roof or side wall for connecting a ventilation duct to the outside air.
- Option G: Drip pan on the interior additionally equipped with a reinforced, fiberglass-reinforced polyester coating to protect the drip pan(s) against the effects of chemicals. List of resistant materials available upon request.
- Option RC: drip pan equipped with a galvanized grating floor R2.40/30x30 mm with a load-bearing capacity of 2300 kg/m² under evenly distributed load and a point load of 425 kg measured over an area of 200x200 mm.
- Option S: interior surfaces of the walls, roof, and door fully finished with galvanized sheet metal.
- Option W: fire-resistant partition wall for compartmentalizing incompatible combinations of hazardous substances.

Option A is available exclusively for the Bigsaver® models BS1, BS2, BS3, BS4, BS5, and BS6.
Option B is available exclusively for the Bigsaver® models BS3, BS4, BS5, and BS6 on the long side.
C Available exclusively for Bigsaver® model BS and BS-L fire compartments.

Foundation:

- Hiltra Bigsaver fire compartments must be installed on a poured concrete foundation. The

foundation must be constructed in accordance with standard NEN 2747, flatness class 2, but limited to a maximum deviation of 5 mm over the entire length and/or width of the structure itself. It is recommended that the foundation be at least 250 mm larger than the outer dimensions of the structure itself. Claims attributable to an improper foundation are not covered by the warranty.

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 1-14



Size Hiltra® Bigsaver® F60 model BS 1-14

Article number	200150200
Fire resistance	F60 in accordance with NEN6069 (Efectis report.)
External dimensions LxWxH	approx. 1420 x 1030 x 2250 mm
Internal dimensions LxWxH	approx. 1165 x 695 x 1720 mm
Daylight size single door W=1300 mm	approx. 1150 x 1890 mm (WxH)
Step height	approx. 315 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized grid
Collection tray content	approx. 220 liters
Weight	approx. 420 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 1-25



Size Hiltra® Bigsaver® F60 model BS 1-25

Article number	200150250
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 1420 x 1440 x 2250 mm
Internal dimensions LxWxH	approx. 1165 x 1105 x 1850 mm
Daylight size single door W=1300 mm	approx. 1150 x 1890 mm (WxH)
Step height	approx. 210 mm
Load-bearing capacity grid floor	approx. 820 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 165 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized grid
Collection tray content	approx. 220 liters
Weight	approx. 530 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 1



Size Hiltra® Bigsaver® F60 model BS 1

Article number	210110200
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 2090 x 1140 x 2250 mm
Internal dimensions LxWxH	approx. 1830 x 800 x 1855 mm
Daylight size single door W=1300 mm	approx. 1170 x 1890 mm (WxH)
Step height	approx. 185 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized grid floor
Collection tray content	approx. 220 liters
Weight	approx. 610 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 2



Size Hiltra® Bigsaver® F60 model BS 2

Article number	210220200
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 2090 x 2170 x 2250 mm
Internal dimensions LxWxH	approx. 1810 x 1810 x 1925 mm
Daylight size single door W=1300 mm	approx. 1170 x 1890 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 at evenly distributed load
Point load grid floor 20x20 cm	approx. 230 kg at evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 250 liters
Weight	approx. 1020 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 2-L



Size Hiltra® Bigsaver® F60 model BS 2-L

Article number	200220210
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 2090 x 2170 x 2610 mm
Internal dimensions LxWxH	approx. 1810 x 1810 x 2290 mm
Daylight size double door W=1800 mm	approx. 1620 x 2260 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 at evenly distributed load
Point load grid floor 20x20 cm	approx. 230 kg at evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 250 liters
Weight	approximately 1170 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 2-XL



Size Hiltra® Bigsaver® F60 model BS 2-XL

Article number	200220315
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 2460 x 2170 x 2610 mm
Internal dimensions LxWxH	approx. 2180 x 1810 x 2285 mm
Daylight size double door W=1800 mm	approx. 1620 x 2260 mm (WxH)
Step height	approx. 120 mm
Load-bearing capacity grid floor	approx. 1475 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 300 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 295 liters
Weight	approx. 1360 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 3



Size Hiltra® Bigsaver® F60 model BS 3

Article number	300220200
Fire Resistance	F60 in accordance with NEN 6069 (Efectis report)
External Dimensions (L x W x H)	approx. 3010 x 2170 x 2250 mm
Internal Dimensions: L x W x H	approx. 2730 x 1810 x 1925 mm
Single-door opening width B=1300 mm, available with either the long or short side	approx. 1170 x 1890 mm (W x H)
Step Height	approx. 115 mm
Load-bearing capacity of a grating floor	approx. 1,300 kg/m² with an evenly distributed load
Point Load on a 20x20 cm Grating Floor	approx. 230 kg with an evenly distributed load
Drip tray	Sandblasted steel, painted, with galvanized grates
Capacity of the collection tray	approx. 380 liters
Weight	approx. 1,390 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 3-L



Size Hiltra® Bigsaver® F60 model BS 3-L

Article number	300220210
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 3010 x 2170 x 2610 mm
Internal dimensions LxWxH	approx. 2730 x 1810 x 2290 mm
Daylight double door B=1800 mm, optionally in long or short side	approx. 1620 x 2260 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 380 liters
Weight	approx. 1540 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 3-XL



Size Hiltra® Bigsaver® F60 model BS 3-XL

Article number	300220315
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 3010 x 2540 x 2610 mm
Internal dimensions LxWxH	approx. 2730 x 2180 x 2285 mm
Daylight double door B=1800 mm, optionally in long or short side	approx. 1620 x 2260 mm (WxH)
Step height	approx. 120 mm
Load-bearing capacity grid floor	approx. 1475 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 300 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 455 liters
Weight	approx. 1760 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 4



Size Hiltra® Bigsaver® F60 model BS 4

Article number	400220200
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 4050 x 2170 x 2250 mm
Internal dimensions LxWxH	approx. 3770 x 1810 x 1925 mm
Daylight size single door B=1300 mm, optionally in long or short side	approx. 1170 x 1890 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg/m2 with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 525 liters
Weight	approx. 1800 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 4-L



Size Hiltra® Bigsaver® F60 model BS 4-L

Article number	400220210
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 4050 x 2170 x 2610 mm
Internal dimensions LxWxH	approx. 3770 x 1810 x 2290 mm
Daylight double door B=1800, optionally in long or short side	approx. 1620 x 2260 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 525 liters
Weight	approx. 1950 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 4-XL



Size Hiltra® Bigsaver® F60 model BS 4-XL

Article number	400220315
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 4050 x 2540 x 2610 mm
Internal dimensions LxWxH	approx. 3770 x 2180 x 2285 mm
Daylight double door B=1800 mm, optionally in long or short side	approx. 1620 x 2260 mm (WxH)
Load-bearing capacity grid floor	approx. 1475 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 300 kg with evenly distributed load
Step height	approx. 120 mm
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 630 liters
Weight	approx. 2210 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 5



Size Hiltra® Bigsaver® F60 model BS 5

Article number	500220200
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 5090 x 2170 x 2250 mm
Internal dimensions LxWxH	approx. 4810 x 1810 x 1925 mm
Daylight size single door B=1300 mm, optionally in long or short side	approx. 1170 x 1890 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 665 liters
Weight	approx. 2210 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 5-L



Size Hiltra® Bigsaver® F60 model BS 5-L

Article number	500220210
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 5090 x 2170 x 2610 mm
Internal dimensions LxWxH	approx. 4810 x 1810 x 2290 mm
Daylight double door B=1800 mm, optionally in long or short side	approx. 1620 x 2260 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg with evenly distributed load
Collection tray	Blasted steel painted with galvanized gratings
Collection tray content	approx. 665 liters
Weight	approx. 2360 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 5-XL



Size Hiltra® Bigsaver® F60 model BS 5-XL

Article number	500220315
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 5090 x 2540 x 2610 mm
Internal dimensions LxWxH	approx. 4810 x 2180 x 2285 mm
Daylight double door B=1800 mm, optionally in long or short side	approx. 1620 x 2260 mm (WxH)
Step height	approx. 120 mm
Load-bearing capacity grid floor	approx. 1475 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 300 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 800 liters
Weight	approx. 2670 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 6



Size Hiltra® Bigsaver® F60 model BS 6

Article number	600220200
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 6010 x 2170 x 2250 mm
Internal dimensions LxWxH	approx. 5730 x 1810 x 1925 mm
Daylight size single door B=1300 mm, optionally in long or short side	approx. 1170 x 1890 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 230 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 800 liters
Weight	approx. 2580 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 6-L



Size Hiltra® Bigsaver® F60 model BS 6-L

Article number	600220210
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 6010 x 2170 x 2610 mm
Internal dimensions LxWxH	approx. 5730 x 1810 x 2290 mm
Daylight double door B=1800 mm, optionally in long or short side	approx.1620 x 2260 mm (WxH)
Step height	approx. 115 mm
Load-bearing capacity grid floor	approx. 1300 kg/m2 at evenly distributed load
Point load grid floor 20x20 cm	approx. 230 kg at evenly distributed load
Collection tray	Blasted beam, painted with galvanized gratings
Collection tray content	approx. 800 liters
Weight	approx. 2730 kg

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 28-11-2026 16:28:49 |
Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Hiltra® Bigsaver® F60 model BS 6-XL



Size Hiltra® Bigsaver® F60 model BS 6-XL

Article number	600220315
Fire resistance	F60 in accordance with NEN6069 (Efectis report)
External dimensions LxWxH	approx. 6010 x 2540 x 2610 mm
Internal dimensions LxWxH	approx. 5730 x 2180 x 2285 mm
Daylight double door B=1800 mm, optionally in long or short side	approx. 1620 x 2260 mm (WxH)
Step height	approx. 120 mm
Load-bearing capacity grid floor	approx. 1475 kg/m2 with uniformly distributed load
Point load grid floor 20x20 cm	approx. 300 kg with evenly distributed load
Collection tray	Blasted steel, painted with galvanized gratings
Collection tray content	approx. 965 liters
Weight	approx. 3110 kg