



Hiltru Barneveld b.v.  
Compagnieweg 14-16  
NL-3771 NH Barneveld  
+ 31 (0)342-404160

[www.hiltru.com](http://www.hiltru.com)  
[info@hiltru.com](mailto:info@hiltru.com)

Created on: 16-06-2026 13:34:59 |  
Technical changes and imperfections  
reserved.

## **Specifications Drip trays for racking**

---

If existing racking systems are to be used for the storage of hazardous substances, they must be fitted with drip trays. The drip trays will be placed on the floor between the racking uprights. The products shown are applicable within the PGS 15 regulations.

### Features:

- Receptacles type BW, manufactured from 3 mm hot-dipped galvanised steel S235JR.
- Collection tray type HLB, manufactured from 2 mm galvanised steel S235JR.
- Underride height 100 mm, ensures easy movement.
- Load-bearing capacity of grid floor (optional) up to 1000 kg/m<sup>2</sup> with evenly distributed load.




Hiltru Barneveld b.v.  
Compagnieweg 14-16  
NL-3771 NH Barneveld  
+ 31 (0)342-404160

www.hiltru.com  
info@hiltru.com

Created on: 16-06-2026 13:34:59 |  
Technical changes and imperfections  
reserved.

## PRODUCT DATA SHEET Hiltru®: Drip tray for pallet rack HLB 12



Size Drip tray for pallet rack HLB 12

Article number	135165003
Discounted shipping costs >	Shipping costs are the same for orders up to 8 pieces !
External dimensions LxDxH	2650 x 1300 x 483 mm
Underride height	100 mm
Collection capacity	1100 liters
Weight	approximately 207 kg
Implementation	galvanized, including galvanized grid floor
Suitable for field width	2700 mm
Size between legs	± 2x 1085 and 1x 835 mm