

Hiltra Barneveld b.v. Compagnieweg 14-16 NL-3771 NH Barneveld + 31 (0)342-404160

Created on: 21-09-2025 20:27:43 | Technical changes and imperfections

reserved.

PRODUCT DATA SHEET Hiltra®: Chemical container type CC 4 (ISO)



Size Chemical container type CC 4 (ISO)

Article number 400230200

External dimensions LxWxH 4050 x 2170 x 2250 mm

Dimensions internal LxWxH 3770 x 1810 x 1940 mm

Load capacity of slatted floor 1300 kg/m2

Collection box Painted steel, W=1300 mm

Contents collection box 525 litres

Weight 1280 litres

Lockable, B=1300 mm

Specifications Chemical container type CC 4 (ISO)

<u>Chemical containers thermally insulated:</u>

Outer casing:

- Designed as a non-fireproof storage container in accordance with directive PGS 15.
- Housing with static strength calculation made from galvanised sheet piling.

Door

• The roof is equipped with an integrated rain gutter on both long sides.

Insulation:

- Walls, roof and door leaves insulated with 40 mm sandwich panels with a core of polyurethane hard foam (insulation value
- 0.47 W/m2K).

Doors:

- Single sash door 1300 mm, fitted with latch and lockable by cylinder lock.
- Double-leaf door; Right door leaf 1300 mm fitted with latch, emergency release and lockable by cylinder lock; Left door leaf 500 mm fitted with internal espagnolette lock.

Drip tray:

- Liquid-tight collection tray manufactured from sheet steel degreased and preserved with an 80 µm two-component zinc phosphate coating in RAL 7040/ window grey.
- Sump provided with a galvanized grid floor R2.30/ mesh size 30x60 mm with a load capacity 1000 kg/m² with evenly distributed load.

Ventilation:

• Natural ventilation and de-aeration through diametrically arranged ventilation openings on the inside and outside provided with paddle grids.

Miscellaneous:

- Standard equipped with lifting device suitable for empty transport.
- Standard equipped with an earth connection point.
- Hazard designation by means of pictograms in accordance with PGS 15.