

Created on: 18-05-2024 22:46:45 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: ST 5000 chemical container



Size ST 5000 chemical container

Article number	31986
External dimensions LxWxH	5080 x 6520 x 2300 mm
Dimensions internal LxWxH	5000 x 6350 x 2000 mm
Load capacity of slatted floor	1000 kg/m ²
Drip trays	Galvanised steel 3 mm with galvanised gratings
Contents collection trays	3x 1480 litres
Weight	3520 kg
Door	Lockable, B=1300 mm

Specifications ST 5000 chemical container

[Chemical containers modularly connected:](#)

Certification:

- Designed as a non-fireproof storage container in accordance with the directive PGS 15.
- General approval of the German Institute for Structural Engineering, DIBt Berlin.

Housing (walls, roof and door):

- Door, walls and roof manufactured from a hot-dip galvanised sheet piling.
- The roof is equipped with an integrated rain gutter on both long sides.
- Maximum roof load (snow load) 100 kg/m².
- Maximum wind load on the walls: $w = 0.40 \text{ KN/m}^2$.
- Maximum wind suction on roof and walls: $w = -0,25 \text{ KN/m}^2$.

Door:

- In the short side a single wing door 1300x1890 mm, with handle, panic lock on the inside and lockable with a cylinder.
- inside and lockable with a cylinder lock.

Drip tray:

- Liquid tight drip tray made of 3 mm steel plate with removable grid floor.
- galvanised grid floor.
- Sump with liquid-tightness certificate issued by TÜV Rheinland e.V.

Ventilation openings:

- Natural ventilation through openings under the roof and above the collection tray.

Hazard identification:

- Hazard indication by pictograms in accordance with PGS 15.

Installation/delivery:

- The individual modules are transported and delivered packaged or (pre-)assembled. The modules are assembled at your site.