

Created on: 03-05-2024 12:08:11 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltra®: Chemotainer model CT 4-1100 (ISO)**

Size Chemotainer model CT 4-1100 (ISO)

Article number	CT4CI1100
Dimensions external WxDxH	3005 x 1600 x 3735 mm
Box dimensions BxDxH	1350 x 1400 x 1500 mm
Storage capacity	4x IBC
Collection capacity	1100 litres
Load capacity of slatted floor	1250 kg/m <sup>2</sup>
Weight	1270 kg
Door	Lockable sliding doors

**Specifications Chemotainer model CT 4-1100 (ISO)**

Version 1.3 | 28-11-2018

[Chemotainer™ ISO compartments \(sliding doors\)](#)

**Basis of calculation:**

- Structural strength calculation (for the chosen application) in accordance with the Buildings Decree and the following European and Dutch standards for steel structures and when anchored to a level and levelled concrete floor.
- NEN-EN 1990+A1/C2:2011: Eurocode 0 - Basis of structural design, including national annex NB:2011. Some basic parameters: design life 15 years, impact class CC1.
- NEN-EN 1991-1-1+C1:2011 Eurocode 1: Loads on structures - Part 1-1: General loads - Masses, dead weights and imposed loads for buildings, including national annex NB:2011.
- NEN-EN 1991-1-3+C1:2011 Eurocode 1: Loads on structures - Part 1-3: General loads - Snow loads, including national annex NB:2011.
- NEN-EN 1991-1-4+A1+C2:2011 Eurocode 1: Loads on structures - Part 1-4: General loads - Wind loads, including national annex NB:2011. Some basic parameters: Wind area 2, Terrain category II, unbuilt.
- NEN-EN 1993-1-1+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-1: General rules and regulations for buildings, including national annex NB:2011.
- NEN-EN 1993-1-8+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-8: Design and calculation of connections, including national annex NB:2011.

**Design:**

- Suitable for two-layer storage of (palletised) packaged hazardous substances.
- Fixed welded-in storage layers (the standard useful height distribution per layer can be changed on request).
- Load-bearing capacity of the slatted floor per storage layer up to 1,250 kg/m<sup>2</sup> with evenly distributed load.
- Point load of the grid floor up to 250 kg measured on a 200x200 mm surface.

### **Main Bearing Structure:**

- Welded steel main frame manufactured in SA2.5 bright steel and treated with a 100 µm Acraton zinc phosphate epoxy coating in RAL 7005/grey.

### **Housing:**

- Roof, walls and sliding doors based on 40 mm aligned ALUzink AZ185 sandwich panels (0.40/0.55 mm board thickness) with a core of insulating (H)CFC-free PIR-Plus rigid foam.
- Fire behaviour classification: B, s2-dO (flame retardant according to EN 13501-1).
- Insulation value [W/m<sup>2</sup>K]: 0, 70 (according to EN 150-10211).
- Sound reduction value: approx. 25 dB(A).
- Corner and finishing strips and fixings on the outside in the same finish as the panels.

### **Sliding door(s):**

- Chemotainer<sup>TM</sup> model CT4, CT8 and CT12 executed with 2-part, manually operated sliding door with handles and centrally lockable with padlock incl. 2 keys.
- Sliding doors are hung on galvanised rails on double adjustable runners.
- Sliding doors are guided at the bottom over the entire width over a guiding profile.

### **Wing door(s):**

- Chemotainer<sup>TM</sup> model CT6 executed with two-part, manually operated hinged door with espagnolette lock and handle with built-in lock incl. 2 keys.

### **Drip trays:**

- First storage layer provided with removable, liquid tight welded drip tray(s) made of blank steel plate.
- Drip tray degreased and coated with approx. 80 µm zinc phosphate epoxy coating in RAL 7040/window grey.

### **Grid floors (on drip tray and second layer):**

- Drip tray(s) and 2nd storage layer provided with removable, galvanised grid floor segments, type R2.40/30x60 mm.

### **Ventilation openings:**

- Natural ventilation and de-aeration through diametrical ventilation grids (high/low).

### **Grounding, anchoring:**

- Standard equipped with base plates for anchoring to the foundation (excluding anchors).
- Earthing via the base plate and foundation anchor.

### **Lifting facility:**

- Standard equipped with four lifting eyes on the roof surface to allow the unit to be craned empty.

**Hazard indication:**

- Hazard indication by pictograms Ø or ? 200 mm, symbol: "smoking and open fire prohibited" and "flammable substances" (other pictograms available on request).

**Construction Options:**

- Option A1: exterior, except for the top of the roof, painted in a standard colour of your choice.
- Option G: drip tray fitted on the inside with a fibreglass-reinforced polyester coating to protect it against chemical attack. Resistance list on request.

Created on: 03-05-2024 12:08:11 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemotainer model CT 6-1100 (ISO)**

Size Chemotainer model CT 6-1100 (ISO)

Article number	CT6CI1100
Dimensions external WxDxH	4140 x 1490 x 3580 mm
Box dimensions BxDxH	3900 x 1400 x 1490 mm
Storage capacity	6x IBC, 6x chemical or 8x euro pallet
Collection capacity	1100 litres
Load capacity of slatted floor	1250 kg/m <sup>2</sup>
Weight	1610 kg
Door	Lockable wing door

**Specifications Chemotainer model CT 6-1100 (ISO)**

Version 1.3 | 28-11-2018

[Chemotainer™ ISO compartments \(sliding doors\)](#)

**Basis of calculation:**

- Structural strength calculation (for the chosen application) in accordance with the Buildings Decree and the following European and Dutch standards for steel structures and when anchored to a level and levelled concrete floor.
- NEN-EN 1990+A1/C2:2011: Eurocode 0 - Basis of structural design, including national annex NB:2011. Some basic parameters: design life 15 years, impact class CC1.
- NEN-EN 1991-1-1+C1:2011 Eurocode 1: Loads on structures - Part 1-1: General loads - Masses, dead weights and imposed loads for buildings, including national annex NB:2011.
- NEN-EN 1991-1-3+C1:2011 Eurocode 1: Loads on structures - Part 1-3: General loads - Snow loads, including national annex NB:2011.
- NEN-EN 1991-1-4+A1+C2:2011 Eurocode 1: Loads on structures - Part 1-4: General loads - Wind loads, including national annex NB:2011. Some basic parameters: Wind area 2, Terrain category II, unbuilt.
- NEN-EN 1993-1-1+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-1: General rules and regulations for buildings, including national annex NB:2011.
- NEN-EN 1993-1-8+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-8: Design and calculation of connections, including national annex NB:2011.

**Design:**

- Suitable for two-layer storage of (palletised) packaged hazardous substances.
- Fixed welded-in storage layers (the standard useful height distribution per layer can be changed on request).
- Load-bearing capacity of the slatted floor per storage layer up to 1,250 kg/m<sup>2</sup> with evenly distributed load.
- Point load of the grid floor up to 250 kg measured on a 200x200 mm surface.

**Main Bearing Structure:**

- Welded steel main frame manufactured in SA2.5 bright steel and treated with a 100 µm Acraton zinc phosphate epoxy coating in RAL 7005/grey.

**Housing:**

- Roof, walls and sliding doors based on 40 mm aligned ALUzink AZ185 sandwich panels (0.40/0.55 mm board thickness) with a core of insulating (H)CFC-free PIR-Plus rigid foam.
- Fire behaviour classification: B, s2-dO (flame retardant according to EN 13501-1).
- Insulation value [W/m<sup>2</sup>K]: 0, 70 (according to EN 150-10211).
- Sound reduction value: approx. 25 dB(A).
- Corner and finishing strips and fixings on the outside in the same finish as the panels.

**Sliding door(s):**

- Chemotainer<sup>TM</sup> model CT4, CT8 and CT12 executed with 2-part, manually operated sliding door with handles and centrally lockable with padlock incl. 2 keys.
- Sliding doors are hung on galvanised rails on double adjustable runners.
- Sliding doors are guided at the bottom over the entire width over a guiding profile.

**Wing door(s):**

- Chemotainer<sup>TM</sup> model CT6 executed with two-part, manually operated hinged door with espagnolette lock and handle with built-in lock incl. 2 keys.

**Drip trays:**

- First storage layer provided with removable, liquid tight welded drip tray(s) made of blank steel plate.
- Drip tray degreased and coated with approx. 80 µm zinc phosphate epoxy coating in RAL 7040/window grey.

**Grid floors (on drip tray and second layer):**

- Drip tray(s) and 2nd storage layer provided with removable, galvanised grid floor segments, type R2.40/30x60 mm.

**Ventilation openings:**

- Natural ventilation and de-aeration through diametrical ventilation grids (high/low).

**Grounding, anchoring:**

- Standard equipped with base plates for anchoring to the foundation (excluding anchors).
- Earthing via the base plate and foundation anchor.

**Lifting facility:**

- Standard equipped with four lifting eyes on the roof surface to allow the unit to be craned empty.

**Hazard indication:**

- Hazard indication by pictograms Ø or ? 200 mm, symbol: "smoking and open fire prohibited" and "flammable substances" (other pictograms available on request).

**Construction Options:**

- Option A1: exterior, except for the top of the roof, painted in a standard colour of your choice.
- Option G: drip tray fitted on the inside with a fibreglass-reinforced polyester coating to protect it against chemical attack. Resistance list on request.

Created on: 03-05-2024 12:08:11 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemotainer model CT 8-2200 (ISO)**

Size Chemotainer model CT 8-2200 (ISO)

Article number	CT8CI100
Dimensions external WxDxH	5875 x 1600 x 3735 mm
Box dimensions BxDxH	2800 x 1400 x 1500 mm
Storage capacity	8x IBC or 8x chemical or 12x europallet
Collection capacity	2x 1100 litres
Load capacity of slatted floor	1250 kg/m <sup>2</sup>
Weight	2270 kg
Door	Lockable sliding doors

**Specifications Chemotainer model CT 8-2200 (ISO)**

Version 1.3 | 28-11-2018

[Chemotainer™ ISO compartments \(sliding doors\)](#)

**Basis of calculation:**

- Structural strength calculation (for the chosen application) in accordance with the Buildings Decree and the following European and Dutch standards for steel structures and when anchored to a level and levelled concrete floor.
- NEN-EN 1990+A1/C2:2011: Eurocode 0 - Basis of structural design, including national annex NB:2011. Some basic parameters: design life 15 years, impact class CC1.
- NEN-EN 1991-1-1+C1:2011 Eurocode 1: Loads on structures - Part 1-1: General loads - Masses, dead weights and imposed loads for buildings, including national annex NB:2011.
- NEN-EN 1991-1-3+C1:2011 Eurocode 1: Loads on structures - Part 1-3: General loads - Snow loads, including national annex NB:2011.
- NEN-EN 1991-1-4+A1+C2:2011 Eurocode 1: Loads on structures - Part 1-4: General loads - Wind loads, including national annex NB:2011. Some basic parameters: Wind area 2, Terrain category II, unbuilt.
- NEN-EN 1993-1-1+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-1: General rules and regulations for buildings, including national annex NB:2011.
- NEN-EN 1993-1-8+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-8: Design and calculation of connections, including national annex NB:2011.

**Design:**

- Suitable for two-layer storage of (palletised) packaged hazardous substances.
- Fixed welded-in storage layers (the standard useful height distribution per layer can be changed on request).
- Load-bearing capacity of the slatted floor per storage layer up to 1,250 kg/m<sup>2</sup> with evenly distributed load.
- Point load of the grid floor up to 250 kg measured on a 200x200 mm surface.

**Main Bearing Structure:**

- Welded steel main frame manufactured in SA2.5 bright steel and treated with a 100 µm Acraton zinc phosphate epoxy coating in RAL 7005/grey.

**Housing:**

- Roof, walls and sliding doors based on 40 mm aligned ALUzink AZ185 sandwich panels (0.40/0.55 mm board thickness) with a core of insulating (H)CFC-free PIR-Plus rigid foam.
- Fire behaviour classification: B, s2-dO (flame retardant according to EN 13501-1).
- Insulation value [W/m<sup>2</sup>K]: 0, 70 (according to EN 150-10211).
- Sound reduction value: approx. 25 dB(A).
- Corner and finishing strips and fixings on the outside in the same finish as the panels.

**Sliding door(s):**

- Chemotainer<sup>TM</sup> model CT4, CT8 and CT12 executed with 2-part, manually operated sliding door with handles and centrally lockable with padlock incl. 2 keys.
- Sliding doors are hung on galvanised rails on double adjustable runners.
- Sliding doors are guided at the bottom over the entire width over a guiding profile.

**Wing door(s):**

- Chemotainer<sup>TM</sup> model CT6 executed with two-part, manually operated hinged door with espagnolette lock and handle with built-in lock incl. 2 keys.

**Drip trays:**

- First storage layer provided with removable, liquid tight welded drip tray(s) made of blank steel plate.
- Drip tray degreased and coated with approx. 80 µm zinc phosphate epoxy coating in RAL 7040/window grey.

**Grid floors (on drip tray and second layer):**

- Drip tray(s) and 2nd storage layer provided with removable, galvanised grid floor segments, type R2.40/30x60 mm.

**Ventilation openings:**

- Natural ventilation and de-aeration through diametrical ventilation grids (high/low).

**Grounding, anchoring:**

- Standard equipped with base plates for anchoring to the foundation (excluding anchors).
- Earthing via the base plate and foundation anchor.

**Lifting facility:**



- Standard equipped with four lifting eyes on the roof surface to allow the unit to be craned empty.

**Hazard indication:**

- Hazard indication by pictograms Ø or ? 200 mm, symbol: "smoking and open fire prohibited" and "flammable substances" (other pictograms available on request).

**Construction Options:**

- Option A1: exterior, except for the top of the roof, painted in a standard colour of your choice.
- Option G: drip tray fitted on the inside with a fibreglass-reinforced polyester coating to protect it against chemical attack. Resistance list on request.

Created on: 03-05-2024 12:08:11 |  
Technical changes and imperfections  
reserved.

**PRODUCT DATA SHEET Hiltru®: Chemotainer model CT 12-2200 (ISO)**

Size Chemotainer model CT 12-2200 (ISO)

Article number	CT12CI100
Dimensions external WxDxH	8125 x 1600 x 3735 mm
Box dimensions BxDxH	3900 x 1400 x 1540 mm
Storage capacity	12x IBC, 12x chemical or 16x euro pallet
Collection capacity	2x 1100 litres
Load capacity of slatted floor	1250 kg/m <sup>2</sup>
Weight	3190 kg
Door	Lockable sliding doors

**Specifications Chemotainer model CT 12-2200 (ISO)**

Version 1.3 | 28-11-2018

[Chemotainer™ ISO compartments \(sliding doors\)](#)

**Basis of calculation:**

- Structural strength calculation (for the chosen application) in accordance with the Buildings Decree and the following European and Dutch standards for steel structures and when anchored to a level and levelled concrete floor.
- NEN-EN 1990+A1/C2:2011: Eurocode 0 - Basis of structural design, including national annex NB:2011. Some basic parameters: design life 15 years, impact class CC1.
- NEN-EN 1991-1-1+C1:2011 Eurocode 1: Loads on structures - Part 1-1: General loads - Masses, dead weights and imposed loads for buildings, including national annex NB:2011.
- NEN-EN 1991-1-3+C1:2011 Eurocode 1: Loads on structures - Part 1-3: General loads - Snow loads, including national annex NB:2011.
- NEN-EN 1991-1-4+A1+C2:2011 Eurocode 1: Loads on structures - Part 1-4: General loads - Wind loads, including national annex NB:2011. Some basic parameters: Wind area 2, Terrain category II, unbuilt.
- NEN-EN 1993-1-1+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-1: General rules and regulations for buildings, including national annex NB:2011.
- NEN-EN 1993-1-8+C2:2011 Eurocode 3: Design and calculation of steel structures - Part 1-8: Design and calculation of connections, including national annex NB:2011.

**Design:**

- Suitable for two-layer storage of (palletised) packaged hazardous substances.
- Fixed welded-in storage layers (the standard useful height distribution per layer can be changed on request).
- Load-bearing capacity of the slatted floor per storage layer up to 1,250 kg/m<sup>2</sup> with evenly distributed load.
- Point load of the grid floor up to 250 kg measured on a 200x200 mm surface.

**Main Bearing Structure:**

- Welded steel main frame manufactured in SA2.5 bright steel and treated with a 100 µm Acraton zinc phosphate epoxy coating in RAL 7005/grey.

**Housing:**

- Roof, walls and sliding doors based on 40 mm aligned ALUzink AZ185 sandwich panels (0.40/0.55 mm board thickness) with a core of insulating (H)CFC-free PIR-Plus rigid foam.
- Fire behaviour classification: B, s2-dO (flame retardant according to EN 13501-1).
- Insulation value [W/m<sup>2</sup>K]: 0, 70 (according to EN 150-10211).
- Sound reduction value: approx. 25 dB(A).
- Corner and finishing strips and fixings on the outside in the same finish as the panels.

**Sliding door(s):**

- Chemotainer<sup>TM</sup> model CT4, CT8 and CT12 executed with 2-part, manually operated sliding door with handles and centrally lockable with padlock incl. 2 keys.
- Sliding doors are hung on galvanised rails on double adjustable runners.
- Sliding doors are guided at the bottom over the entire width over a guiding profile.

**Wing door(s):**

- Chemotainer<sup>TM</sup> model CT6 executed with two-part, manually operated hinged door with espagnolette lock and handle with built-in lock incl. 2 keys.

**Drip trays:**

- First storage layer provided with removable, liquid tight welded drip tray(s) made of blank steel plate.
- Drip tray degreased and coated with approx. 80 µm zinc phosphate epoxy coating in RAL 7040/window grey.

**Grid floors (on drip tray and second layer):**

- Drip tray(s) and 2nd storage layer provided with removable, galvanised grid floor segments, type R2.40/30x60 mm.

**Ventilation openings:**

- Natural ventilation and de-aeration through diametrical ventilation grids (high/low).

**Grounding, anchoring:**

- Standard equipped with base plates for anchoring to the foundation (excluding anchors).
- Earthing via the base plate and foundation anchor.

**Lifting facility:**

- Standard equipped with four lifting eyes on the roof surface to allow the unit to be craned empty.

**Hazard indication:**

- Hazard indication by pictograms Ø or ? 200 mm, symbol: "smoking and open fire prohibited" and "flammable substances" (other pictograms available on request).

**Construction Options:**

- Option A1: exterior, except for the top of the roof, painted in a standard colour of your choice.
- Option G: drip tray fitted on the inside with a fibreglass-reinforced polyester coating to protect it against chemical attack. Resistance list on request.