

Created on: 27-10-2025 21:22:16 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: Emergency shower frost proof MB 200



Size Emergency shower frost proof MB 200

Article number	999999979
Material	Plastic outer jacket
Pipework	Galvanized
Operation	Stainless steel pull handle
Water flow	80 l/min. (2 Bar G)
Water supply	1¼" BSP internal thread
Nutrition	230 Volt suitable for Normal Zone.
Frost-free	to -30°

Specifications Emergency shower frost proof MB 200

Oog- en nooddouches voor industriële toepassing op locaties waar kans op bevriezing aanwezig is. Door het toepassen van (trace-tape) isolatie wordt hiervoor optimale bescherming geboden. Getoonde producten zijn toepasbaar binnen de PGS 15 regelgeving.

Features:

- Design according to ANSI Z 358.1 and CE EN 15154.
- Executed with galvanized or stainless steel piping in insulated plastic outer jacket.
- Suitable for outdoor use up to a temperature of -30°C.
- Pipework protected from frost by means of self-regulating heating ribbon.
- Body shower equipped with a special plastic shower head with 60° rotation for fast effective operation.
- Eyebath with double spray head placed in a impact resistant plastic container with a hinged lid.
- Eyebath equipped with perlators/diffusers for a pleasant, sparkling and oxygenated water spray.
- Delivery in package, assembly and connection must be provided by the client.
- Atex version on request.