


Created on: 27-10-2025 21:19:07 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: Eye wash MBS 60 (stainless steel)



Size Eye wash MBS 60 (stainless steel)

Article number	999999979
Material	Plastic eyebath and outer jacket
Pipework	RVS
Operation	Lid control
Water flow	12 l/min.
Water supply	1¼" BSP internal thread
Nutrition	230 Volt suitable for Normal Zone
Frost-free	Up to -30°

Specifications Eye wash MBS 60 (stainless steel)

Oog- en nooddouches voor industriële toepassing op locaties waar kans op bevriezing aanwezig is. Door het toepassen van (trace-tape) isolatie wordt hiervoor optimale bescherming geboden. Getoonde producten zijn toepasbaar binnen de PGS 15 regelgeving.

Features:

- Design according to ANSI Z 358.1 and CE EN 15154.
- Executed with galvanized or stainless steel piping in insulated plastic outer jacket.
- Suitable for outdoor use up to a temperature of -30°C.
- Pipework protected from frost by means of self-regulating heating ribbon.
- Body shower equipped with a special plastic shower head with 60° rotation for fast effective operation.
- Eyebath with double spray head placed in a impact resistant plastic container with a hinged lid.
- Eyebath equipped with perlators/diffusers for a pleasant, sparkling and oxygenated water spray.
- Delivery in package, assembly and connection must be provided by the client.
- Atex version on request.