

Created on: 27-10-2025 21:16:04 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: Eye and emergency shower MBS 250-50 -RVS (-30°)



Size Eye and emergency shower MBS 250-50 -RVS (-30°)

Article number	999999979
Material	Eye bath and outer jacket and shower head made of plastic
Piping	STAINLESS STEEL
Operation	Shower stainless steel pull handle. Eye bath lid control
Water yield	Shower 80 ltr/min, Bath 12 ltr/min.
Water supply	1¼" BSP internal thread
Nutrition	230 Volt suitable for Normal Zone
Frost-free	Up to -30°

Specifications Eye and emergency shower MBS 250-50 -RVS (-30°)

Oog- en nooddouches voor industriële toepassing op locaties waar kans op bevriezing aanwezig is. Door het toepassen van (trace-tape) isolatie wordt hiervoor optimale bescherming geboden. Getoonde producten zijn toepasbaar binnen de PGS 15 regelgeving.

Features:

- Design according to ANSI Z 358.1 and CE EN 15154.
- Executed with galvanized or stainless steel piping in insulated plastic outer jacket.
- Suitable for outdoor use up to a temperature of -30°C.
- Pipework protected from frost by means of self-regulating heating ribbon.
- Body shower equipped with a special plastic shower head with 60° rotation for fast effective operation.
- Eyebath with double spray head placed in a impact resistant plastic container with a hinged lid.
- Eyebath equipped with perlators/diffusers for a pleasant, sparkling and oxygenated water spray.
- Delivery in package, assembly and connection must be provided by the client.
- Atex version on request.