

Created on: 04-05-2024 07:29:59 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: Atex fan ENG 3-6

Size Atex fan ENG 3-6

Article number	190170520
Connection	230 V / 50 Hz
Engine output	120 watts
Nenstroom	1,07 A
Nominal capacity	430 m ³ / hour
Max.pressure difference	340 Pa
IP Class	IP 54
Sound pressure level (engine only)	± 65 dB(A)
Flange connection	Ø 100 mm (both sides)
Atex classification	Ex II 2 Gc T4
Weight	6,6 kg

Specifications Atex fan ENG 3-6

In order to prevent dangerous situations caused by explosive or harmful air mixtures, a storage room for dangerous substances must be ventilated effectively. The most common models are available separately to equip your existing storage space. Of course, the products shown can be used within the PGS 15 regulations.

Features:

- Available in Eex and SWD (splash water protected) versions.
- Fans made of steel (stainless steel or plastic on request).
- Also available Atex motor protection/work switch.
- Also available Atex wall socket.
- Also available: Atex on/off switch and Atex power box.
- Optional mounting bracket available.

Optional

Option description	Option article number
Mounting foot lacquered for Atex ENG 3-6	190171520