

Created on: 20-05-2024 11:32:11 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltra®: Material container combi MC 1360



Size Material container combi MC 1360

Article number	1360
External dimensions LxWxH	3050 x 6520 x 2150 mm
Dimensions internal LxWxH	2920 x 6350 x 2000 mm
Weight	960 kg
Single door WxH	1300 x 1890 mm
Floor area approx.	18 m ²
Delivery	Standard in package, assembly optional (request)

Specifications Material container combi MC 1360

Version 2.0 - 29-07-2019

[FLADAFI® MATERIAL CONTAINERS:](#)

Fladafi Material Containers can be used anywhere where materials and tools must be stored theft-proof and protected from the weather. must be stored. These include building sites, industrial companies petrol pumps and schools.

- Material containers (except the combi models) are fitted as standard, but can always be dismantled.
- Standard equipped with lifting eyes for (empty) transport (except the combi models).
- Unique construction with statistical calculation
- Side walls, door and roof made of sendzimir galvanized steel trapezoidal profiles.
- Roof with integrated Rain gutters, drain opening at every corner of the roof
- Max. snowload roof 220 kg/m²
- Floor consists of a stable wooden construction with crossbars and planed planks on one side with tongue and groove connection.
- Max. distributed load on the floor 500 kg/m²
- Wind load: 0.59 kn/m² (wind zone 2, inland)
- Earthquake load: Earthquake zone 3, category II.
- Low maintenance.
- Optionally available at extra cost Available at extra cost (among other things):
 - Crane facility for lifting container including loading
 - Forklift tracks

- Exterior paintwork in standard RAL colour: RAL 1003/yellow, RAL 3000/red 3000/red, RAL 5010/blue, RAL 6010/green, RAL 7035/light grey, RAL 9002/grey white. Other colours on request
- Various design options