

Created on: 12-07-2025 11:40:32 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltra®: Rolling door box RB 1100



Size Rolling door box RB 1100

Article number	9511
Dimensions DxWxH external	2100 x 1140 x 2320 mm
Dimensions DxWxH internal	2000 x 970 x 2000 mm
Rolling door	in 2100 mm side
Weight	150 kg
Delivery	Mounted

Specifications Rolling door box RB 1100

Version 1.0 - 25-06-2019

FLADAFI® MATERIAL CONTAINER WITH ROLL CLOSURE:

- Suitable for indoor and outdoor installation.
- Space-saving through the use of an aluminium roller shutter.
- Used as a material storage container and also suitable for waste bins (120/240 litres).
- Galvanised steel sheet piling construction with wooden floor.
- Developed technology through decades of experience in container construction.
- Floor made of stable wooden frame with cross members and 20 mm tongue-and-groove planed planks on one side, load bearing capacity up to 500 kg/m² (distributed).
- Accessible roof with rain gutters on both sides, suitable for a snow load of 220 kg/m².
- Aluminium roller shutter with guiding system including spring box, mini blades with handle, continuously adjustable.
- Shutter opening 1800 mm wide.
- Two-point locking on the outside including security lock.
- Assembled delivery.
- Unique construction developed and produced by Sabu with static calculation.
- Optional: exterior paintwork in a standard RAL colour: RAL 1003, RAL 3000, RAL 5010, RAL 6010, RAL 7035 and RAL 9002.
- Other RAL colours on request.
- CE-marking with declaration of performance according to Eurocode 3.

Created on: 12-07-2025 11:40:32 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: Rolling door box RB 1200



Size Rolling door box RB 1200

Article number	9512
Dimensions LxWxH external	2100 x 2170 x 2320 mm
Dimensions LxWxH internal	2000 x 2000 x 2000 mm
Rolling door	in the 2100 mm side
Weight	300 kg
Delivery	Mounted

Specifications Rolling door box RB 1200

Version 1.0 - 25-06-2019

FLADAFI® MATERIAL CONTAINER WITH ROLL CLOSURE:

- Suitable for indoor and outdoor installation.
- Space-saving through the use of an aluminium roller shutter.
- Used as a material storage container and also suitable for waste bins (120/240 litres).
- Galvanised steel sheet piling construction with wooden floor.
- Developed technology through decades of experience in container construction.
- Floor made of stable wooden frame with cross members and 20 mm tongue-and-groove planed planks on one side, load bearing capacity up to 500 kg/m² (distributed).
- Accessible roof with rain gutters on both sides, suitable for a snow load of 220 kg/m².
- Aluminium roller shutter with guiding system including spring box, mini blades with handle, continuously adjustable.
- Shutter opening 1800 mm wide.
- Two-point locking on the outside including security lock.
- Assembled delivery.
- Unique construction developed and produced by Sabu with static calculation.
- Optional: exterior paintwork in a standard RAL colour: RAL 1003, RAL 3000, RAL 5010, RAL 6010, RAL 7035 and RAL 9002.
- Other RAL colours on request.
- CE-marking with declaration of performance according to Eurocode 3.

Created on: 12-07-2025 11:40:32 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltra®: Rolling door box RB 1300



Size Rolling door box RB 1300

Article number	9513
Dimensions LxWxH external	3050 x 2170 x 2320 mm
Dimensions LxWxH internal	2920 x 2000 x 2000 mm
Rolling door	in 2100 mm side
Weight	450 kg
Delivery	Mounted

Specifications Rolling door box RB 1300

Version 1.0 - 25-06-2019

FLADAFI® MATERIAL CONTAINER WITH ROLL CLOSURE:

- Suitable for indoor and outdoor installation.
- Space-saving through the use of an aluminium roller shutter.
- Used as a material storage container and also suitable for waste bins (120/240 litres).
- Galvanised steel sheet piling construction with wooden floor.
- Developed technology through decades of experience in container construction.
- Floor made of stable wooden frame with cross members and 20 mm tongue-and-groove planed planks on one side, load bearing capacity up to 500 kg/m² (distributed).
- Accessible roof with rain gutters on both sides, suitable for a snow load of 220 kg/m².
- Aluminium roller shutter with guiding system including spring box, mini blades with handle, continuously adjustable.
- Shutter opening 1800 mm wide.
- Two-point locking on the outside including security lock.
- Assembled delivery.
- Unique construction developed and produced by Sabu with static calculation.
- Optional: exterior paintwork in a standard RAL colour: RAL 1003, RAL 3000, RAL 5010, RAL 6010, RAL 7035 and RAL 9002.
- Other RAL colours on request.
- CE-marking with declaration of performance according to Eurocode 3.