

Created on: 04-05-2024 12:20:15 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltru®: Labsaver F90 LS620-EN - Li-ion - RAL7035/Grey - STORAGE BASIC PLUS



Size Labsaver F90 LS620-EN - Li-ion - RAL7035/Grey -
STORAGE BASIC PLUS

Article number	060600221
Cabinet certification	F90 according to EN 14470-1
Certification Emergency pressure relief	EI-90 in accordance with 1634-1
Dimensions external WxDxH	approx. 600 x 600 x 2035 mm
Dimensions internal BxDxH	approx. 492 x 450 x 1724 mm
Self-closing door	Single, right-hinged, lockable with cylinder lock
Standard equipped with:	Fire resistant emergency hatch incl. filter, 1x approx. 200 x 200 mm
	Emergency hatch including cover and flange connection Ø 125 mm
	Thermal door interlock
	4x double PE-coated grid shelves
Grid Shelf BxDxH	approx. 466 x 425 x 25 mm
Load capacity shelves	up to 75 kg when evenly distributed
Own weight	approx. 250 kg
Packaging and transport	on pallet, upright H=2200 mm

Specifications Labsaver F90 LS620-EN - Li-ion - RAL7035/Grey - STORAGE BASIC PLUS

Optional

Option description	Option article number
Security P1 for LS620 - Li-ion	06600226
Security P2 for LS620 - Li-ion	06600227
Security P3 for LS620 -Li-ion	060600228
SMS alarm module for external alarms (only in combination with P3 or A3)	060600230
Stainless steel transport base for LS620	060600225
HF filter cassette in the cover (Basic Plus only > against hydrogen fluoride emissions)	06600232
Additional shelf for LS620 - Li-ion	060200224