


Hiltra Barneveld b.v. Compagnieweg 14-16 NL-3771 NH Barneveld + 31 (0)342-404160

Created on: 18-05-2024 17:41:03 | Technical changes and imperfections reserved.

## PRODUCT DATA SHEET Hiltra®: Hiltra F60 gas bottle depot model BSG 6-bw





Size Hiltra F60 gas bottle depot model BSG 6-bw	
Article number	600220366
Dimensions external WxDxH	6010 x 2170 x 2240 mm
Dimensions internal BxDxH	1840/1840 x 1800 x 1925 mm
Capacity	168x 50 litre standard cylinder (3x 56 pieces)
Weight	approx. 2900 kg
Door	Lockable single door B=1300 mm with emergency release
Fire resistance	F60 according to NEN6069 : 2005 (Efectis report)

## Specifications Hiltra F60 gas bottle depot model BSG 6-bw

Version 1.1 | 11-07-2023

HILTRA® BIGSAVER® MODEL BSG GENERAL

## **Design/fire resistance:**

- The composite structure was assessed by the accredited testing institute Efectis®.
- Efectis brandwerendheidsrapport: 94-CVB-R1178/2009-Efectis-R0834(Rev.1)/2010-Efectis-R1117-S.
- Designed as an independent fire compartment for the storage of packaged hazardous materials based on the Building Code and guideline PGS 15: 2016 version 1.0.
- Fire resistance (WBDBO) 60 minutes determined in case of a fire from outside and a fire from inside on all criteria of PGS 15:2016 version 1.0, regulation 3.2.9.

## Housing (walls, roof and door):

- Casing made of galvanized sheet piling.
- Interior made of non-combustible and insulating material finished with galvanized sheet.
- The roof is equipped with an integrated rain gutter on both long sides.