

Created on: 05-07-2025 23:32:05 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltra®: F30 Hiltra display cabinet model 100

Size F30 Hiltra display cabinet model 100

Article number	999999994
Dimensions external WxDxH	605 x 550 x 1980 mm
Storage capacity	130 litres
Adjustable shelves 30 x 490 x 410 mm	steel, 3 pieces
Bottom tray incl. perforated cover	steel, 1 piece
Capacity baking tray	30 kg (distributed load)
Weight	approx. 170 kg

Specifications F30 Hiltra display cabinet model 100

Version 1.0 | 1-1-2020

[F30 Hiltra® display cabinets](#)

Certification:

- Tested and approved F30 according to EN-14470-1 (04-2004) and EN 1363-1 (06-2000).
- Tested and approved F10 in accordance with FM 6050 (Factory Mutual international) - Additional certification in progress.
- Standard cabinet labelling according to ISO 3864 and EN 14470-1 (04-2004) standards and 92/58/CEE 'european directive' and FM regulation.

Features:

- 30 minutes fire resistance according to the ISO 834 fire curve.
- Can be driven under by forklift/pallet truck by removing the front panel (bottom).
- Self-closing doors which can be locked open. At a temperature of approx. 43°C, the door(s) will close automatically. (Door closer(s) with temperature fuse).
- Glass in the door(s) for a good view on the stored products.

Passive safety:

- Cabinet finish melamine: corrosion-resistant with good chemical-resistant properties.
- Cupboard colour RAL735/light grey, with corners RAL1023/yellow.
- Door(s) with fire resistant glass, thickness 17 mm.

- Safety marking according to EN 14470-1 and FM 6050.
- Height adjustable shelves (per 32 mm).
- Base of the cabinet provided with a removable drip tray and perforated cover plate.

Active safety:

- Ventilation flanges Ø 100 mm for connection to external air or mechanised extraction (fan).
- Self-closing door(s).
- Door(s) equipped with 3-point locking.
- Sparkproof locking system.
- Base of cabinet fitted with adjustable feet.

Optional:

- Additional tray shelf(s).
- Extendable shelves (automatically reversible).
- PVC shelves and bottom collection tray.
- Simple connection for an exhaust system or fan filter box.

Optional

Option description	Option article number
Extra tray board 30x490x410 mm for display cabinet model 100	999999994
Extendable shelf 80x420x380 mm for display cabinet model 100	999999994
Shelf PVC 30x485x405 mm for display cabinet model 100	999999994
Bottom tray PVC 100x485x405 mm for display cabinet model 100	999999994

Created on: 05-07-2025 23:32:05 |
Technical changes and imperfections
reserved.

PRODUCT DATA SHEET Hiltra®: F30 Hiltra display cabinet model 150



Size F30 Hiltra display cabinet model 150

Article number	999999994
Dimensions external WxDxH	1115 x 550 x 1980 mm
Storage capacity	250 litres
Adjustable shelves 30 x 990 x 410 mm	3 pieces
Bottom tray incl. perforated plate	1 piece
Capacity baking tray	50 kg (distributed load)
Weight	approx. 255 kg

Specifications F30 Hiltra display cabinet model 150

Version 1.0 | 1-1-2020

[F30 Hiltra® display cabinets](#)

Certification:

- Tested and approved F30 according to EN-14470-1 (04-2004) and EN 1363-1 (06-2000).
- Tested and approved F10 in accordance with FM 6050 (Factory Mutual international) - Additional certification in progress.
- Standard cabinet labelling according to ISO 3864 and EN 14470-1 (04-2004) standards and 92/58/CEE 'european directive' and FM regulation.

Features:

- 30 minutes fire resistance according to the ISO 834 fire curve.
- Can be driven under by forklift/pallet truck by removing the front panel (bottom).
- Self-closing doors which can be locked open. At a temperature of approx. 43°C, the door(s) will close automatically. (Door closer(s) with temperature fuse).
- Glass in the door(s) for a good view on the stored products.

Passive safety:

- Cabinet finish melamine: corrosion-resistant with good chemical-resistant properties.
- Cupboard colour RAL735/light grey, with corners RAL1023/yellow.
- Door(s) with fire resistant glass, thickness 17 mm.

- Safety marking according to EN 14470-1 and FM 6050.
- Height adjustable shelves (per 32 mm).
- Base of the cabinet provided with a removable drip tray and perforated cover plate.

Active safety:

- Ventilation flanges Ø 100 mm for connection to external air or mechanised extraction (fan).
- Self-closing door(s).
- Door(s) equipped with 3-point locking.
- Sparkproof locking system.
- Base of cabinet fitted with adjustable feet.

Optional:

- Additional tray shelf(s).
- Extendable shelves (automatically reversible).
- PVC shelves and bottom collection tray.
- Simple connection for an exhaust system or fan filter box.

Optional

Option description	Option article number
Additional shelving 30x1000x410 mm for display cabinet model 150	999999994
Pull-out shelf 80x930x380 mm for display cabinet model 150	999999994
2x PVC shelves 30x485x405 mm for display cabinet model 150 (for 1 shelf)	999999994
2x floor collector PVC 100x485x405 mm for display cabinet model 150 (for 1 shelf)	999999994