Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 03-08-2025 23:40:59 | Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Chemical cabinet type CK10

Inzetrooster en PE-antislipmat zijn optioneel

Size Chemical cabinet type CK10

Article number	500500100
Certification	GS / Tüv
Dimensions external WxDxH	500 x 500 x 1020 mm
Dimensions internal BxDxH	498 x 453 x 855 mm
Contents tray board	10 litres
Shelf boards BxDxH	490 x 450 x 70 mm
Color	RAL 7035/light grey
Weight	30 kg
Standard equipment	2x tray shelf (WHG)

Specifications Chemical cabinet type CK10

Chemical cabinets CK series:

- On the entire cabinet Tüv / GS approval. (Does not apply to the CK40-TM)
- Cabinets only suitable for indoor application.
- Constructed in accordance with the regulations in the PGS 15 guideline.
- Suitable for ADR class substances for which no fire safety cabinet is required.
- Housing made entirely of powder coated steel.
- Front with single or double hinged door with 3-point locking.
- Door equipped with Ergo-lock handle with built-in cylinder lock incl. 2 keys. (CK40-TM plastic/aluminium lock)
- Shelves and shelves of galvanized steel, adjustable in 50 mm increments. (CK40-TM> steel powder coated)
- Container trays liquid-tight with tested according to WHG (TÜV). (CK40-TM is without TÜV certificate)
- Container trays and shelves suitable for evenly distributed loads of up to 70 kg.
- Natural ventilation and de-aeration through air vents in the door.
- Hazard warning through pictogram: "Fire, naked flame and smoking prohibited".

Optional

Option description	Option article number
Shelf 10L (extra) WxD 490x450 mm	500500101
Insert grid for shelves BxD 490x450 mm	500500102
PE drip tray 10L incl. shelf BxD 490x450 mm	500500103
PE anti-slip mat for roof area CK10	500500104
	888888879

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 03-08-2025 23:40:59 | Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Chemical cabinet type CK20 - grey

Size Chemical cabinet type CK20 - grey

Article number	500500195
Certification	GS / Tüv
Dimensions external WxDxH	500 x 500 x 1950 mm
Dimensions internal BxDxH	498 x 453 x 1840 mm
Contents tray board	10 litres
Shelf boards BxDxH	490 x 450 x 70 mm
Color	RAL 7035/light grey
Weight	48 kg
Standard equipment	4x shelves (WHG)

Specifications Chemical cabinet type CK20 - grey

Chemical cabinets CK series:

- On the entire cabinet Tüv / GS approval. (Does not apply to the CK40-TM)
- Cabinets only suitable for indoor application.
- Constructed in accordance with the regulations in the PGS 15 guideline.
- Suitable for ADR class substances for which no fire safety cabinet is required.
- Housing made entirely of powder coated steel.
- Front with single or double hinged door with 3-point locking.
- Door equipped with Ergo-lock handle with built-in cylinder lock incl. 2 keys. (CK40-TM plastic/aluminium lock)
- Shelves and shelves of galvanized steel, adjustable in 50 mm increments. (CK40-TM> steel powder coated)
- Container trays liquid-tight with tested according to WHG (TÜV). (CK40-TM is without TÜV certificate)
- Container trays and shelves suitable for evenly distributed loads of up to 70 kg.
- Natural ventilation and de-aeration through air vents in the door.
- Hazard warning through pictogram: "Fire, naked flame and smoking prohibited".

Optional

Option description	Option article number
Shelf 10L (extra) WxD 490x450 mm	500500101
Insert grid for shelves BxD 490x450 mm	500500102
PE drip tray 10L incl. shelf BxD 490x450 mm	500500103
	888888879

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

PRODUCT DATA SHEET Hiltra®: Chemical cabinet type CK20 - green

Size Chemical cabinet type CK20 - green

Article number	500502195
Certification	GS / Tüv
Dimensions external WxDxH	500 x 500 x 1950 mm
Dimensions internal BxDxH	498 x 453 x 1840 mm
Contents tray board	10 litres
Shelf boards BxDxH	490 x 450 x 70 mm
Color	RAL 6011/green
Weight	48 kg
Standard equipment	4x shelves (WHG)

Specifications Chemical cabinet type CK20 - green

Chemical cabinets CK series:

- On the entire cabinet Tüv / GS approval. (Does not apply to the CK40-TM)
- Cabinets only suitable for indoor application.
- Constructed in accordance with the regulations in the PGS 15 guideline.
- Suitable for ADR class substances for which no fire safety cabinet is required.
- Housing made entirely of powder coated steel.
- Front with single or double hinged door with 3-point locking.
- Door equipped with Ergo-lock handle with built-in cylinder lock incl. 2 keys. (CK40-TM plastic/aluminium lock)
- Shelves and shelves of galvanized steel, adjustable in 50 mm increments. (CK40-TM> steel powder coated)
- Container trays liquid-tight with tested according to WHG (TÜV). (CK40-TM is without TÜV certificate)
- Container trays and shelves suitable for evenly distributed loads of up to 70 kg.
- Natural ventilation and de-aeration through air vents in the door.
- Hazard warning through pictogram: "Fire, naked flame and smoking prohibited".

Optional

Option description	Option article number
Shelf 10L (extra) WxD 490x450 mm	500500101
Insert grid for shelves BxD 490x450 mm	500500102
PE drip tray 10L incl. shelf BxD 490x450 mm	500500103
	888888879

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 03-08-2025 23:40:59 | Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Chemical cabinet type CK30

Inzetrooster en PE-antislipmat zijn optioneel.

Size Chemical cabinet type CK30

Article number	950500100
Certification	GS / Tüv
Dimensions external WxDxH	930 x 500 x 1020 mm
Dimensions internal BxDxH	928 x 453 x 855 mm
Contents tray board	20 litres
Shelf boards BxDxH	920 x 450 x 70 mm
Color	RAL 7035/light grey
Weight	47 kg
Standard equipment	2x tray shelf (WHG)

Specifications Chemical cabinet type CK30

Chemical cabinets CK series:

- On the entire cabinet Tüv / GS approval. (Does not apply to the CK40-TM)
- Cabinets only suitable for indoor application.
- Constructed in accordance with the regulations in the PGS 15 guideline.
- Suitable for ADR class substances for which no fire safety cabinet is required.
- Housing made entirely of powder coated steel.
- Front with single or double hinged door with 3-point locking.
- Door equipped with Ergo-lock handle with built-in cylinder lock incl. 2 keys. (CK40-TM plastic/aluminium lock)
- Shelves and shelves of galvanized steel, adjustable in 50 mm increments. (CK40-TM> steel powder coated)
- Container trays liquid-tight with tested according to WHG (TÜV). (CK40-TM is without TÜV certificate)
- Container trays and shelves suitable for evenly distributed loads of up to 70 kg.
- Natural ventilation and de-aeration through air vents in the door.
- Hazard warning through pictogram: "Fire, naked flame and smoking prohibited".

Optional

Option description	Option article number
Shelf 20 L (extra) WxD 920x450 mm	950500101
Insert grid for shelves BXD 920x450 mm	950500102
PE tray board 20 L incl. shelf BXD 920x450 mm	950500103
Shelf flat (extra) BxD 920x450 mm	950500105
PE anti-slip mat for roof area CK30	950500104
	888888879

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

Created on: 03-08-2025 23:40:59 | Technical changes and imperfections reserved.

PRODUCT DATA SHEET Hiltra®: Chemical cabinet type CK40-LB

Size Chemical cabinet type CK40-LB

Article number	950502195
Certification	GS / Tüv
Dimensions external WxDxH	930 x 500 x 1950 mm
Dimensions internal BxDxH	928 x 453 x 1840 mm
Contents Bottom tray	20 litres
Shelf BxD	925 x 452 mm
Color	Carcase RAL 7035/light grey, doors: RAL 1023/yellow
Weight	approx. 74 kg
Standard equipment	3x shelf (flat), 1x floor drip tray (WHG)

Specifications Chemical cabinet type CK40-LB

Chemical cabinets CK series:

- On the entire cabinet Tüv / GS approval. (Does not apply to the CK40-TM)
- Cabinets only suitable for indoor application.
- Constructed in accordance with the regulations in the PGS 15 guideline.
- Suitable for ADR class substances for which no fire safety cabinet is required.
- Housing made entirely of powder coated steel.
- Front with single or double hinged door with 3-point locking.
- Door equipped with Ergo-lock handle with built-in cylinder lock incl. 2 keys. (CK40-TM plastic/aluminium lock)
- Shelves and shelves of galvanized steel, adjustable in 50 mm increments. (CK40-TM> steel powder coated)
- Container trays liquid-tight with tested according to WHG (TÜV). (CK40-TM is without TÜV certificate)
- Container trays and shelves suitable for evenly distributed loads of up to 70 kg.
- Natural ventilation and de-aeration through air vents in the door.
- Hazard warning through pictogram: "Fire, naked flame and smoking prohibited".

Optional

Option description	Option article number
Shelf 20 L (extra) WxD 920x450 mm	950500101
Insert grid for shelves BXD 920x450 mm	950500102
PE tray board 20 L incl. shelf BXD 920x450 mm	950500103
Shelf flat (extra) BxD 920x450 mm	950500105

PRODUCT DATA SHEET Hiltra®: Chemical cabinet type CK40 - grey

Size Chemical cabinet type CK40 - grey

Article number	950500195
Certification	GS / Tüv
Dimensions external WxDxH	930 x 500 x 1950 mm
Dimensions internal BxDxH	928 x 453 x 1840 mm
Contents tray board	20 litres
Shelf boards BxDxH	920 x 450 x 70 mm
Color	RAL 7035/light grey
Weight	76 kg
Standard equipment	4x shelves (WHG)

Specifications Chemical cabinet type CK40 - grey

Chemical cabinets CK series:

- On the entire cabinet Tüv / GS approval. (Does not apply to the CK40-TM)
- Cabinets only suitable for indoor application.
- Constructed in accordance with the regulations in the PGS 15 guideline.
- Suitable for ADR class substances for which no fire safety cabinet is required.
- Housing made entirely of powder coated steel.
- Front with single or double hinged door with 3-point locking.
- Door equipped with Ergo-lock handle with built-in cylinder lock incl. 2 keys. (CK40-TM plastic/aluminium lock)
- Shelves and shelves of galvanized steel, adjustable in 50 mm increments. (CK40-TM> steel powder coated)
- Container trays liquid-tight with tested according to WHG (TÜV). (CK40-TM is without TÜV certificate)
- Container trays and shelves suitable for evenly distributed loads of up to 70 kg.
- Natural ventilation and de-aeration through air vents in the door.
- Hazard warning through pictogram: "Fire, naked flame and smoking prohibited".

Optional

Option description	Option article number
Shelf 20 L (extra) WxD 920x450 mm	950500101
Insert grid for shelves BXD 920x450 mm	950500102
PE tray board 20 L incl. shelf BXD 920x450 mm	950500103
Shelf flat (extra) BxD 920x450 mm	950500105
	888888879

Hiltra Barneveld b.v.
Compagnieweg 14-16
NL-3771 NH Barneveld
+ 31 (0)342-404160

www.hiltra.com
info@hiltra.com

PRODUCT DATA SHEET Hiltra®: Chemical cabinet type CK40 - green

Size Chemical cabinet type CK40 - green

Article number	950503195
Certification	GS / Tüv
Dimensions external WxDxH	930 x 500 x 1950 mm
Dimensions internal BxDxH	928 x 453 x 1840 mm
Contents tray board	20 litres
Shelf boards BxDxH	920 x 450 x 70 mm
Color	RAL 6011/green
Weight	76 kg
Standard equipment	4x shelves (WHG)

Specifications Chemical cabinet type CK40 - green

Chemical cabinets CK series:

- On the entire cabinet Tüv / GS approval. (Does not apply to the CK40-TM)
- Cabinets only suitable for indoor application.
- Constructed in accordance with the regulations in the PGS 15 guideline.
- Suitable for ADR class substances for which no fire safety cabinet is required.
- Housing made entirely of powder coated steel.
- Front with single or double hinged door with 3-point locking.
- Door equipped with Ergo-lock handle with built-in cylinder lock incl. 2 keys. (CK40-TM plastic/aluminium lock)
- Shelves and shelves of galvanized steel, adjustable in 50 mm increments. (CK40-TM> steel powder coated)
- Container trays liquid-tight with tested according to WHG (TÜV). (CK40-TM is without TÜV certificate)
- Container trays and shelves suitable for evenly distributed loads of up to 70 kg.
- Natural ventilation and de-aeration through air vents in the door.
- Hazard warning through pictogram: "Fire, naked flame and smoking prohibited".

Optional

Option description	Option article number
Shelf 20 L (extra) WxD 920x450 mm	950500101
Insert grid for shelves BXD 920x450 mm	950500102
PE tray board 20 L incl. shelf BXD 920x450 mm	950500103
Shelf flat (extra) BxD 920x450 mm	950500105
	888888879